



# HANDYBOARD 10mm WALL BOARD

## PRODUCT TECHNICAL STATEMENT

HandyBoard™ 10mm Wall Board is Mitre10's most cost effective plasterboard, ideal for small DIY and large projects alike.

### USE

HandyBoard™ 10mm Wall Board is suitable for use in all commercial and residential situations provided that its specification and installation is in accordance with AS/NZS 2589:2017 Standard.

When installing HandyBoard™ Wall Board in an existing building, the installer must ensure the framing is suitable for the proposed building work.

### CONDITIONS & LIMITATIONS

The installation of HandyBoard™ 10mm Wall Board must be in accordance with AS/NZS 2589:2017.

HandyBoard™ 10mm Wall Board provides a flat surface for application of decorative finishes such as paint and wallpaper.

HandyBoard™ 10mm Wall Board must not be used in following situations:

- For bracing applications
- In wet areas such as bathrooms and kitchens
- Where a fire resistance rating (FRR) is required
- Where an acoustic rated system is specified
- Applied directly to masonry, concrete or solid plaster
- Used externally of the building envelope
- Exposed to temperatures of 52°C or greater for prolonged periods. (Refer to appliance and fitting manufacturers for installation details.)



### NZBC COMPLIANCE

HandyBoard™ 10mm Wall Board complies with the following performance criteria of the NZ Building Code

PERFORMANCE CRITERIA	EVIDENCE
B1.3.1 B1.3.2 B1.3.3 (a, i) B1.3.4	In respect of building element. Manufactured in accordance with AS/NZS 2588:1998.
B2.3.1(c)	5 years
F2.3.1	Manufactured in accordance with AS/NZS 2588:1998 and will not present a hazard to people.

When installed HandyBoard™ Wall Board will contribute to compliance with the following performance criteria of the NZ Building Code

PERFORMANCE CRITERIA	EVIDENCE
B2.3.1(c)	In Service history

# » PRODUCT TECHNICAL STATEMENT

## PRODUCT DESCRIPTION

BOARD SPECIFICATION	
FEATURE	DESCRIPTION
Thickness	10mm
Edge Profiles	Recessed edge
Sheet Size	1200 x 2400mm & 900 x 1800mm
Paper Colour	Buff
Mass	6.5 kg/m <sup>2</sup> nominal
Manufacture	Manufactured in Indonesia to the requirements of AS/NZS 2588:1998 Gypsum Plasterboard and in accordance with AS/NZS ISO 9001:2008 – Quality management systems – Requirements

## PERFORMANCE DETAILS

### INSTALLATION

HandyBoard™ Wall Board must be installed in accordance with the AS/NZS 2589:2017.

### MAINTENANCE

HandyBoard™ Wall Board does not require maintenance but USG Boral recommend a visual check of the board to be undertaken as part of normal maintenance, for instance when the surface coating is applied. In the event that damage is apparent, the board must be removed and replaced in accordance with the AS/NZS 2589:2017.

## STORAGE & TRANSPORTATION

HandyBoard™ Wall Board, like all plasterboards, is vulnerable to potential in transit damage. It should be transported and stored horizontally. Once onsite, ensure the plasterboard is covered, to avoid possible exposure to moisture.

## QUALITY ASSURANCE

HandyBoard™ Wall Board is manufactured in Indonesia. These manufacturing sites are ISO9001:2008 accredited. Certificate details are SAI Global Cert No. QEC0400. This certification dates from 1992.

## REFERENCES

For more information refer to [handyboard.co.nz](http://handyboard.co.nz)

Test results may be available upon request, providing the information is not commercially sensitive.

## WARRANTY


For details of the HandyBoard warranty refer to [handyboard.co.nz](http://handyboard.co.nz)

## DURABILITY STATEMENT

This statement relates to Clause B2 Durability of the New Zealand Building Code (NZBC). HandyBoard™ Plasterboard is designed for internal use and when installed in accordance with the installation instructions detailed within the relevant Technical Installation literature is fully compliant with the NZBC.

## FURTHER INFORMATION

[handyboard.co.nz](http://handyboard.co.nz)  
0800 874 267



Exclusive to

